



Model

WK1P

Maximum pipe diameter

2" on re-circulating pool systems only

Flow Rate – Flow rate is immaterial as far as Aqua-Rex is concerned. The greater the flow, the more effective the units tend to be.

Product Data

○ Aerial Length	10'
○ Aerial Number	2
○ Minimum aerial turns	12 Turns
○ Frequency range	1 – 10 kHz
○ Peak to peak output voltage	82 V
○ Power supply required	120 V
○ Input current	0.02 A
○ Power consumption	1 W
○ Transformer output	9 V. ac
○ Power cable length	10'
○ Dimensions	5" x 3" x 2"
○ Weight	2lb
○ Ambient temperature	160°F
○ Humidity non-condensing	100%
○ Self-diagnostic guard chip	Yes
○ BMS output	No

Self-Diagnostic "Guard Chip" – Every computer system is prone to malfunction, especially if there is a sudden variation in the power supply, which can jam the program. Most systems have to be reset by manual re-booting. Aqua-Rex units overcome this problem by an additional "Guard Chip" program, which monitors the performance of the main program and resets the system automatically if it detects a variation or system failure. There is no need for manual resetting after power outage.

Maintenance – Once installed, the WK1P requires no maintenance.

Lifecycle costs – Running costs are less than \$30.00 per annum. The design life is in excess of 25 years with a 5-year manufacturer's warranty.



Aqua-Rex LLC
t 1-877 640 2170
c 949 887 2170
e sales@aquar-ex.com
2230 W.Chapman Avenue
Suite 247
Orange, CA 92868