

Model

***SENTRY***

**Maximum pipe diameter**

28mm

**Direct Fired Water Heaters** . We recommend maximum heat rating for different sized units and this also varies according to whether they are gas fired, oil fired or heated electrically.

**Direct fired gas / oil**

35 kW

**Electrical boiler**

15 kW

**Flow Rate** . Flow rate is immaterial as far as Water-King is concerned. The greater the flow, the more effective the units tend to be.

**Product Data**

○ Aerial Length	1.8 m
○ Aerial Number	2
○ Minimum aerial turns	12 Turns
○ Frequency range	1 . 10 kHz
○ Peak to peak output voltage	82 V
○ Power supply required	230 V or 110 V
○ Input current	0.02 A
○ Power consumption	1 W
○ Transformer output	9 V. ac
○ Power cable length	1.5 m
○ Dimensions	140mm x 85mm x 50mm
○ Weight	0.75 kg
○ Ambient temperature	0 . 70 °C
○ Humidity non-condensing	Waterproof
○ Self-diagnostic guard chip	Yes
○ IP Standard	68
○ BMS output	No

**Self-Diagnostic “Guard Chip”** . Every computer system is prone to malfunction, especially if there is a sudden variation in the power supply, which can jam the program. Most systems have to reset by manual re-booting. Water-King units overcome this problem by an additional %Guard Chip+program, which monitors the performance of the main program and resets the system automatically if it detects a variation or system failure. There is no need for manual resetting after power outage.

**Maintenance** . Once installed, the Sentry requires no maintenance.

**Lifecycle costs** . Running costs are less than £5.00 per annum. The design life is 25 years with a 5-year manufacturer’s warranty.

**UPC** . 5031476003030